



外形尺寸 OUTER DIMENSIONS

HDW-80

选项功能 OPTION FUNCTION

A	Overall height	1310mm
B	Overall length	2160mm
C	Traverse stroke	1600mm
D	Main-arm vertical stroke	900mm
E	Main-arm vertical standby	170mm
F	Bottom of crosswise to chuck mount position	330mm
G	Base side face to Box end	375mm
H	Sub-arm vertical standby	---
I	Main-arm reach max	680mm
J	Main-arm crosswise stroke max	500mm
K	Main-arm crosswise standby min	180mm
L	Main/Sub-arm proximity min	---
M	Sub-arm crosswise stroke max	---
N	Sub-arm crosswise standby min	---
O	Crosswise arm end to Box end	1170mm

<ul style="list-style-type: none"> □ Air nipper in chuck circuit □ NT □ NT gate cutting on crossmember of moving □ 2 □ Additional vacuum sensing unit 2 circuits □ 2 □ Product gripping 2 circuits □ Mold close during ascend □ Rotation unit □ Ejector return link □ 12 □ EUROMAP 12 □ 67 □ EUROMAP 67

Feature and scope of the product does not guarantee the product attributes only for reference. Our scope of delivery and services provided are based solely on the terms of delivery and services provided are based solely on the terms of the contract. Technical data and illustration are only for reference. We reserve the rights of changing.

TSD-2021-12

广东拓斯达科技股份有限公司
GUANGDONG TOPSTAR TECHNOLOGY CO., LTD.

ADD: No.3 Chuanxin Road, Daomang, Dalingshan Town, Dongguan City,
Guangdong Province

TEL: 0769-8305 0999 FAX: 0769-8584 5562

Domestic Service Hotline: 400-096-8005

